

RFSG-141-25

High performance 25ohm seimi rigid coaxial cable

Ver A/0 Release Date Match, 2015



P/N: 214125

Features&Benefits

- 70%Vp PTFE + Copper tube
- Ultra-low loss, High shield effectiveness
- Equivalent to UT-141-25
- Replace to PE-141SR-25



Construction Specification

	Description	Size (mm)	Tol.	Materials
1	Center conductor	1.65	±0.01	Silver Plated Copper
2	Dielectric	2.99	±0.05	Extruded PTFE
3	Outer conductor	3.56	±0.05	Bare Copper Tube Tinned Seamless annealed copper Zinc & Tinned plated copper

Mechanical&Environmental Specifications

RoHS

Bend Radius:installation (mm)	15	RoHS	Compliant
Bend Radius:repeated (mm)	36		
Weight (g/m)	62 max.		
Temp, Operating&Installation (°C)	-65~165		
Temp, Storage (°C)	-65~165		

Electrical Specifications

Characteristic Impedance(ohm)	25±2	Time delay	4.7
Capacitance(pF/m)	190	Max Working Power(Vrms)	3000
Velocity ratio(%)	70	Shielding Effectiveness(dB)	>110
Cutoff frequency(GHz)	29		

Attenuation (Typical@25°C&VSWR=1.0) &Power (VSWR=1.0;40°C;Sea Level)

Frequency MHz	0.5	1000	5000	10000	18000	26500
dB/100 m	33.1	47.9	114.2	169.6	240.2	304.1
Avg.Power KW	0.473	0.330	0.140	0.095	0.068	0.054

Maximum attenuation is 10% higher.

Defined by: Luke

Prepared by: Eric

Approved by: K.F. Lu

Rev: A/0

Shenzhen RFcoms Technology Co.,LTD

Website: www.rfcoms.com

Tell: +86 13480725660 Fax:+86-755-28908582

Email: luke@rfcoms.com

The rights of technical information provided on this sheet belongs to RFcoms. Contents cannot be distributed to other third-party companies without permission.The specifications are subjected to change without prior notice