

## RFSG-141-35

High performance 35ohm seimi rigid coaxial cable

Ver A/0 Release Date Match, 2015



P/N: 214135

### Features&Benefits

- 70%Vp PTFE + Copper tube
- Ultra-low loss, High shield effectiveness
- Equivalent to UT-141-35
- Replace to PE-141SR-35



### Construction Specification

	Description	Size (mm)	Tol.	Materials
1	Center conductor	1.29	±0.01	Silver Plated Copper
2	Dielectric	2.99	±0.05	Extruded PTFE
3	Outer conductor	3.56	±0.05	Bare Copper Tube Tinned Seamless annealed copper Zinc & Tinned plated copper

### Mechanical&Environmental Specifications

### RoHS

Bend Radius:installation (mm)	15	RoHS	Compliant
Bend Radius:repeated (mm)	36		
Weight (g/m)	56 max.		
Temp, Operating&Installation (°C)	-65~165		
Temp, Storage (°C)	-65~165		

### Electrical Specifications

Characteristic Impedance(ohm)	35±2	Time delay	4.7
Capacitance(pF/m)	135	Max Working Power(Vrms)	2000
Velocity ratio(%)	70	Shielding Effectiveness(dB)	>110
Cutoff frequency(GHz)	31		

### Attenuation (Typical@25°C&VSWR=1.0) &Power (VSWR=1.0;40°C;Sea Level)

Frequency MHz	0.5	1000	5000	10000	18000	26500
dB/100 m	28.2	40.7	98.8	147.6	210.3	268.0
Avg.Power KW	0.553	0.385	0.162	0.109	0.078	0.061

Maximum attenuation is 10% higher.

Defined by: Luke

Prepared by: Eric

Approved by: K.F. Lu

Rev: A/0

Shenzhen RFcoms Technology Co.,LTD

Website: [www.rfcoms.com](http://www.rfcoms.com)

Tell: +86 13480725660 Fax:+86-755-28908582

Email: [luke@rfcoms.com](mailto:luke@rfcoms.com)

The rights of technical information provided on this sheet belongs to RFcoms. Contents cannot be distributed to other third-party companies without permission.The specifications are subjected to change without prior notice