

RG178DS

High performance 50ohm flexible coaxial cable


Ver A/0 Release Date Match, 2018



P/N: 3178D

Features&Benefits

- 70%Vp PTFE+ Double TPC Wire Braiding
- Low loss, Flexible, Low Cost
- Equivalent to
- Replace to



Construction Specification

	Description	Size (mm)	Tol.	Materials
1	Center conductor	0.306(7*0.102)	±0.01	Silver Plated Copper
2	Dielectric	0.86	±0.05	Extruded PTFE
3	Outer conductor	1.30	±0.05	Silver Plated Copper Shield
4	Outer conductor	1.70	±0.15	Silver Plated Copper Shield
5	Jacket	2.30	±0.15	Fluorinated Ethylene Propylene(FEP) Brown or Transparent Color

Mechanical&Environmental Specifications

RoHS

Bend Radius:installation (mm)	12	RoHS	Compliant
Bend Radius:repeated (mm)	23		
Weight (g/m)	14 max.		
Temp, Operating&Installation (°C)	-55~200(FEP)		
Temp, Storage (°C)	-55~200(FEP)		

Electrical Specifications

Characteristic Impedance(ohm)	50±2	Time delay	4.7
Capacitance(pF/m)	98	Max Working Power(Vrms)	1500
Velocity ratio(%)	70	VSWR(DC~6GHz)	≤1.25
Cutoff frequency(GHz)	114	Shielding Effect(dB @1GHz)	>70

Attenuation (Typical@25°C&VSWR=1.0) &Power (VSWR=1.0;40°C;Sea Level)

Frequency MHz	100	400	900	1000	1800	2400	3000	5000	6000
dB/100 m	58.0	105.0	158.0	168.0	224.0	259.0	291.0	376.0	413.0
Avg.Power kW	0.225	0.115	0.072	0.068	0.047	0.040	0.034	0.026	0.023

Maximum attenuation is 10% higher.

Defined by: Luke

Shenzhen RFcoms Technology Co.,LTD

Prepared by: Eric

Website: www.rfcoms.com

Approved by: K.F. Lu

Tell: +86 13480725660 Fax:+86-755-28908582

Rev: A/0

Email: luke@rfcoms.com

The rights of technical information provided on this sheet belongs to RFcoms. Contents cannot be distributed to other third-party companies without permission.The specifications are subjected to change without prior notice