

RG303

High performance 50ohm flexible coaxial cable

Ver A/0 Release Date Match, 2018



P/N: 3303

Features&Benefits

- 70%Vp PTFE+ Single TPC Wire Braiding
- Low loss, Flexible, Low Cost
- Equivalent to SFF-50-3-1
- Replace to RG303



Construction Specification

	Description	Size (mm)	Tol.	Materials
1	Center conductor	0.94	±0.01	Silver Plated Copper
2	Dielectric	2.98	±0.05	Extruded PTFE
3	Outer conductor	3.45	±0.05	Silver Plated Copper Shield
4	Jacket	4.50	±0.05	Fluorinated Ethylene Propylene(FEP) Brown or Transparent Color

Mechanical&Environmental Specifications

RoHS

Bend Radius:installation (mm)	23	RoHS	Compliant
Bend Radius:repeated (mm)	45		
Weight (g/m)	48 max.		
Temp, Operating&Installation (°C)	-55~200(FEP)		
Temp, Storage (°C)	-55~200(FEP)		

Electrical Specifications

Characteristic Impedance(ohm)	50±2	Time delay	4.7
Capacitance(pF/m)	98	Max Working Power(Vrms)	3000
Velocity ratio(%)	70	VSWR(DC~12.4GHz)	≤1.25
Cutoff frequency(GHz)	6	Shielding Effect(dB @1GHz)	> 60

Attenuation (Typical@25°C&VSWR=1.0) &Power (VSWR=1.0;40°C;Sea Level)

Frequency MHz	100	400	900	1000	1800	2400	3000
dB/100 m	13.0	27.0	43.0	46.0	63.0	72.0	82.0
Avg.Power kW	2.350	1.050	0.640	0.600	0.430	0.350	0.310

Maximum attenuation is 10% higher.

Defined by: Luke

Shenzhen RFcoms Technology Co.,LTD

Prepared by: Eric

Website: www.rfcoms.com

Approved by: K.F. Lu

Tell: +86 13480725660 Fax:+86-755-28908582

Rev: A/0

Email: luke@rfcoms.com

The rights of technical information provided on this sheet belongs to RFcoms. Contents cannot be distributed to other third-party companies without permission.The specifications are subjected to change without prior notice