

## RG400DS

High performance 50ohm flexible coaxial cable


Ver A/0 Release Date Match, 2018



P/N: 3400

### Features&Benefits

- 70%Vp PTFE+ Double TPC Wire Braiding
- Low loss, Flexible, Low Cost
- Equivalent to RG400
- Replace to ENVIROFLEX-400



### Construction Specification

	Description	Size (mm)	Tol.	Materials
1	Center conductor	1.015 (19*0.203)	±0.01	Silver Plated Copper
2	Dielectric	2.98	±0.05	Extruded PTFE
3	Outer conductor	3.45	±0.05	Silver Plated Copper Shield
4	Outer conductor	3.95	±0.05	Silver Plated Copper Shield
5	Jacket	4.95	±0.15	Fluorinated Ethylene Propylene(FEP) Brown or Transparent Color

### Mechanical&Environmental Specifications

### RoHS

Bend Radius:installation (mm)	25	RoHS	Compliant
Bend Radius:repeated (mm)	50		
Weight (g/m)	65 max.		
Temp, Operating&Installation (°C)	-55~200(FEP)		
Temp, Storage (°C)	-55~200(FEP)		

### Electrical Specifications

Characteristic Impedance(ohm)	50±2	Time delay	4.7
Capacitance(pF/m)	105	Max Working Power(Vrms)	2000
Velocity ratio(%)	70	VSWR(DC~6GHz)	≤1.35
Cutoff frequency(GHz)	31	Shielding Effect(dB @1GHz)	>70

### Attenuation (Typical@25°C&VSWR=1.0) &Power (VSWR=1.0;40°C;Sea Level)

Frequency MHz	100	400	900	1000	1800	2400	3000	5000	6000	10000	15000
dB/100 m	15.0	32.0	50.0	52.0	72.0	83.0	94.0	122.0	134.0	205.0	250.0
Avg.Power kW	2.300	1.050	0.660	0.610	0.440	0.380	0.330	0.260	0.220	0.170	0.140

Maximum attenuation is 10% higher.

Defined by: Luke

Shenzhen RFcoms Technology Co.,LTD

Prepared by: Eric

Website: www.rfcoms.com

Approved by: K.F. Lu

Tell: +86 13480725660 Fax:+86-755-28908582

Rev: A/0

Email: luke@rfcoms.com

The rights of technical information provided on this sheet belongs to RFcoms. Contents cannot be distributed to other third-party companies without permission.The specifications are subjected to change without prior notice