

RG330

High performance 50ohm flexible coaxial cable

Ver A/0 Release Date Match, 2018



P/N: 3330

Features&Benefits

- 70%Vp PTFE+ Single TPC Wire Braiding
- Low loss, Flexible, Low Cost
- Equivalent to 0
- Replace to 0



Construction Specification

	Description	Size (mm)	Tol.	Materials
1	Center conductor	0.73	±0.01	Silver Plated Copper
2	Dielectric	2.20	±0.05	Extruded PTFE
3	Outer conductor	2.65	±0.05	Silver Plated Copper Shield
4	Jacket	3.30	±0.05	Fluorinated Ethylene Propylene(FEP) Brown or Transparent Color

Mechanical&Environmental Specifications

RoHS

Bend Radius:installation (mm)	16	RoHS	Compliant
Bend Radius:repeated (mm)	33		
Weight (g/m)	30 max.		
Temp, Operating&Installation (°C)	-55~200(FEP)		
Temp, Storage (°C)	-55~200(FEP)		

Electrical Specifications

Characteristic Impedance(ohm)	50±2	Time delay	4.7
Capacitance(pF/m)	102	Max Working Power(Vrms)	1500
Velocity ratio(%)	70	VSWR(DC~12.4GHz)	≤1.25
Cutoff frequency(GHz)	6	Shielding Effect(dB @1GHz)	>60

Attenuation (Typical@25°C&VSWR=1.0) &Power (VSWR=1.0;40°C;Sea Level)

Frequency MHz	500	1000	1800	2400	3000	5000	6000
dB/100 m	48.0	69.0	94.0	118.0	127.0	157.0	178.0
Avg.Power kW	0.560	0.292	0.230	0.175	0.141	0.095	0.078

Maximum attenuation is 10% higher.

Defined by: Luke

Shenzhen RFcoms Technology Co.,LTD

Prepared by: Eric

Website: www.rfcoms.com

Approved by: K.F. Lu

Tell: +86 13480725660 Fax:+86-755-28908582

Rev: A/0

Email: luke@rfcoms.com

The rights of technical information provided on this sheet belongs to RFcoms. Contents cannot be distributed to other third-party companies without permission.The specifications are subjected to change without prior notice