

AT1550 50Ω 15W 3~40dB DC~52GHz
2.4mm High Performance 50Ohm Stainless Steel Attenuator



Ver A/0 Release Date March, 2018


P/N:AT1550

Features

- DC~52GHz Frequency Range
- Max Power 16W
- VSWR < 1.52 < 1.34 < 1.23 < 1.16
C-Class B-Class A-Class S-Class

Applications

- Miniature Size
- 2.4mm Interfaces
- Instrumentation
- Precision measurements
- Prototyping and characterization
- Production systems



Mechanical & Environmental Specifications

Outer Conductor Coupling Nut	Passivated Stainless Steel	Temp. Range	Storage	-55℃~125℃
Radiator	Black Anodized Aluminum Heatsink	Working Temp.		-55℃~100℃
Inner Conductor Male	Beryllium Copper Gold plated($\geq 1.27\mu\text{m}$)	Altitude	Storage	< 15300 Meters
Female	Beryllium Copper Gold plated($\geq 1.27\mu\text{m}$)	Working Temp.		< 4800 Meters
Weight	53 g			

Electrical Specifications

Model	Frequency Range(GHz)	Attenuation(dBc) and accuracy				Return Loss(dB)
		3~10	20	30	40	
AT1550C-XX	DC~50GHz	-0.8/+2.0	-1.5/+1.8	-1.5/+1.8	-1.5/+1.8	-13.7
AT1550B-XX	DC~50GHz	-1.5/+1.8	-1.2/+1.5	-1.2/+1.5	-1.2/+1.5	-16.8
AT1550A-XX	DC~50GHz	-1.2/+1.5	-1.0/+1.2	-1.0/+1.2	-1.0/+1.2	-19.7
AT1550S-XX	DC~50GHz	-1.0/+1.2	-0.8/+1.0	-0.8/+1.0	-0.8/+1.0	-22.6

XX refers to decrease value,C,B,A,S are average power of performance level.

Average power: The ambient temperature corresponding to bidirectional 16W input or 8W output is 25 °C

When temperature is up to 100℃.The power decreases linearly to 1.5W or 1W

Peak power: Max power 100W (Maximum 5 μs pulse width, maximum 6% or 3% duty cycle)

Working time: no air cooling, ≤ 5 minutes; with air cooling, air volume ≥ 8CFM, long-term work

Remark

- 1、 All physical dimensions are in mm and the tolerance is $\pm 1\%$
- 2、 The network analyzer tests in the whole frequency band, 100% electrical performance test.
- 3、 Special connectors and special attenuation can be customized according to customer requirements

Shenzhen RFcoms Technology Co.,LTD

Tell: +86 13480725660

Website: www.rfcoms.com

Email: luke@rfcoms.com

The rights of technical information provided on this sheet belongs to RFcoms. Contents cannot be distributed to other third-party companies without permission. The specifications are subjected to change without prior notice