

TM0218 50Ω 2W DC~18GHz
N High Performance 50Ohm Stainless Steel Terminator



Ver A/0 Release Date March, 2018



P/N:TM0218

Features

- DC~18GHz Frequency Range
- Max Power 2.5W
- VSWR < 1.20
- Miniature Size
- N Interfaces

Applications

- Wireless
- Radar System
- Commercial and Military
- Test and Measurement
- Communication
- Satcom



Mechanical & Environmental Specifications



Outer Conductor Coupling Nut	Passivated Stainless Steel	Temp. Range	Storage	-55℃~125℃
Body	Passivated Stainless Steel		Working Temp.	-55℃~100℃
Inner Conductor Male	Beryllium Copper Gold plated(≥ 1.27μ m)	Altitude	Storage	< 15300 Meters
Female	Beryllium Copper Gold plated(≥ 1.27μ m)		Working Temp.	< 4800 Meters
Weight	20 g			

Electrical Specifications

Model	Frequency Range(GHz)	VSWR(:1)	Return Loss(dB)
TM0218	DC~18GHz	< 1.20	-24.7

Average power:Max power 2W corresponding ambient temperature is 25℃,Power derates linearly to 0.5W when temperature is up to 100℃.Peak power: Max power 125W (Maximum 5 μ s pulse, maximum 1% duty cycle)

Remark:a.dimension mm, tol. ± 1%. b.100% test. c.Customized according to customer requestments



Shenzhen RFcoms Technology Co.,LTD

Tell: +86 13480725660

Website: www.rfcoms.com

Email: luke@rfcoms.com

The rights of technical information provided on this sheet belongs to RFcoms. Contents cannot be distributed to other third-party companies without permission. The specifications are subjected to change without prior notice