

**AT3030 50Ω 30W 9~30dB DC~30GHz**  
**SMA High Performance 50Ohm Stainless Steel Attenuator**



Ver A/0 Release Date March, 2018


P/N:AT3030

**Features**

- DC~30GHz Frequency Range
- Max Power 20W
- VSWR < 1.20

**Applications**

- Miniature Size
- SMA Interfaces
- Instrumentation
- Precision measurements
- Prototyping and characterization
- Production systems



**Mechanical & Environmental Specifications**

Outer Conductor Coupling Nut	Passivated Stainless Steel	Temp. Range	Storage	-55℃~125℃
Radiator	Black Anodized Aluminum Heatsink	Working Temp.		-55℃~100℃
Inner Conductor Male	Beryllium Copper Gold plated ( $\geq 1.27\mu\text{m}$ )	Altitude	Storage	< 15300 Meters
Female	Beryllium Copper Gold plated ( $\geq 1.27\mu\text{m}$ )	Working Temp.		< 4800 Meters
Weight	130 g			

**Electrical Specifications**

Model	Frequency Range (GHz)	Attenuation(dBc) and accuracy				Return Loss(dB)
		6~9	10	20	30	
AT3030-XX	DC~30GHz	-0.5/+0.5	-0.5/+0.5	-0.5/+0.5	-0.6/+0.6	-24.7

XX refers to decrease value

Average power: The ambient temperature corresponding to bidirectional at 30W input is 25 °C

When temperature is up to 100℃.The power decreases linearly to 3W

Peak power: Max power 200W (Maximum 5  $\mu\text{s}$  pulse width, maximum 10% duty cycle)

Working time: no air cooling,  $\leq 5$  minutes; with air cooling, air volume  $\geq 8\text{CFM}$ , long-term work

**Remark**

- 1、 All physical dimensions are in mm and the tolerance is  $\pm 1\%$
- 2、 The network analyzer tests in the whole frequency band, 100% electrical performance test.
- 3、 Special connectors and special attenuation can be customized according to customer requirements

Shenzhen RFcoms Technology Co.,LTD

Tell: +86 13480725660

Website: www.rfcoms.com

Email: luke@rfcoms.com

The rights of technical information provided on this sheet belongs to RFcoms. Contents cannot be distributed to other third-party companies without permission. The specifications are subjected to change without prior notice