

RFSMU600

高性能低损耗,超柔射频电缆


Ver A/0 发布日期 2015年3月



P/N:4836

产品特点

- 86%Vp FPE介质+自粘铝箔+镀锡铜丝编织
- 超低损耗,低成本,超长寿命
- 等同于 LMR600UF
- 可替换 CDF600UF
CNT600UF



结构尺寸

	结构	尺寸 (mm)	公差	材料
1	中心导体	4.47 (1.56*7)	±0.02	绞线裸铜
2	电介质	11.56	±0.15	发泡PE
3	外导体	11.73	±0.01	自粘铝箔
4	外层屏蔽	12.56	±0.10	镀锡铜丝编织
5	外护套	14.99	±0.15	TPE黑色或定制

机械与环境性能

弯曲半径, 最小安装(mm)
弯曲半径, 重复弯曲(mm)
最大拉伸强度(N)
重量(g/m)
温度范围, 安装与使用(°C)
电缆抗压(负载700N)(%)

38.5
153
1750
165
-40~+85
< 1%

有毒有害物质含量

镉及其化合物 (Cd)	< 0.01%
铅及其化合物 (Pb)	< 0.1%
汞及其化合物 (Hg)	< 0.1%
六价铬及其化合物	< 0.1%
多溴联苯(PBB)	< 0.1%
多溴二苯醚(PBDE)	< 0.1%

电气性能

特性阻抗(ohm)	50±2	绝缘介电强度(V DC)	4000
静电容(pF/m)	77	绝缘电阻(MΩ · km)	> 10,000
传输速率(%)	86	额定功率(KW)	40
内直流电阻(ohm/km)	< 1.7	屏蔽性能(dB)	> 90
外直流电阻(ohm/km)	< 3.9	编织密度(%)	90±3
护套火花电压(V RMS)	8000	驻波比 100-3000 MHz	< 1.25
电感(μH/m)	0.2		

衰减值 (典型值@25°C&VSWR=1.0) 与传输功率值 (典型值@40°C&一个标准大气压下)

频率 MHz	30	50	150	220	450	900	1500	1800	2000	2500	5800
dB/100 m	1.70	2.20	3.80	4.60	6.80	9.80	13.10	14.50	15.30	17.40	28.60
平均功率 kW	4.590	3.530	2.000	1.640	1.120	0.770	0.580	0.520	0.490	0.430	0.260

衰减最大高出10%

Defined by: Luke
Prepared by: Eric
Approved by: K.F. Lu
Rev: A/0

深圳市睿凡讯连科技有限公司
网址: www.rfcoms.com
电话: +86 13480725660
Email: luke@rfcoms.com

RFSMU600

High performance,Ultra Low Loss,Ultra flexible Coax Cable


Ver A/0 Release Date Match, 2015



P/N:4836

Features&Benefits

- 86%Vp FPE+Al Bonded Tape+TC shield
- Ultra-low loss, Less cost,Durable
- Equivalent to LMR600UF
- Replace to CDF600UF
CNT600UF



Construction Specification

	Description	Size (mm)	Tol.	Materials
1	Center conductor	4.47 (1.56*7)	±0.02	Stranded Bare Copper
2	Dielectric	2.95	±0.15	Foam PE
3	Outer conductor	11.73	±0.05	Bonded AL/P-Foil
4	Outer shield	12.56	±0.10	Tinned Copper Shields
5	Jacket	14.99	±0.15	TPE black or customize

Mechanical&Environmental Specifications

Bend Radius:installation (mm)	38.5
Bend Radius:repeated (mm)	153
Max.Pulling Tension (N)	1750
Weight (g/m)	165
Temp, Operating&Installation (°C)	-40~+85
Crush resistance of cable (load of 700N)(%)	<1%

RoHS Guideline

Cadmium content (Cd)	<0.01%
Lead content (Pb)	<0.1%
Mercury content (Hg)	<0.1%
Chromium (VI) content	<0.1%
Polybrominated Biphenyls (PBB)	<0.1%
Polybrominated Diphenyl Ether (PBDE)	<0.1%

Electrical Specifications

Characteristic Impedance(ohm)	50±2	Dielectric Strength(V DC)	4000
Capacitance(pF/m)	77	Insulation resistance(MΩ·km)	>10,000
Velocity ratio(%)	86	Peak Power(KW)	40
DCR: Inner Conductor(ohm/km)	<1.7	Shielding Effectiveness(dB)	>90
DCR: Outer Conductor(ohm/km)	<3.9	Shields Coverage(%)	90±3
Jacket Sparker(V RMS)	8000	SWR 100-3000 MHz	<1.25

Attenuation (Typical@25°C&VSWR=1.0) &Power (VSWR=1.0;40°C;Sea Level)

Frequency MHz	30	50	150	220	450	900	1500	1800	2000	2500	5800
dB/100 m	1.70	2.20	3.80	4.60	6.80	9.80	13.10	14.50	15.30	17.40	28.60
Avg.Power kW	4.590	3.530	2.000	1.640	1.120	0.770	0.580	0.520	0.490	0.430	0.260

Maximum attenuation is 10% higher.

Defined by: Luke

Prepared by: Eric

Approved by: K.F. Lu

Rev: A/0

Shenzhen RFcoms Technology Co.,LTD

Website: www.rfcoms.com

Tel: +86 13480725660

Email: luke@rfcoms.com

The rights of technical information provided on this sheet belongs to RFcoms. Contents cannot be distributed to other third-party companies without permission.The specifications are subjected to change without prior notice